

**\*\* READ & SAVE THESE INSTRUCTIONS \*\***  
**HALOGEN FLUSH MOUNTS**  
**ASSEMBLY AND INSTALLATION INSTRUCTIONS**

**(1) TOOLS AND MATERIALS REQUIRED**

- BLADE SCREW DRIVER
- ADJUSTABLE WRENCH
- STEP LADDER
- WIRING SUPPLIES AS REQUIRED BY ELECTRICAL CODE

**CAUTION**

BEFORE ASSEMBLING YOUR LIGHTING FIXTURE PLEASE READ THE INSTRUCTIONS. IF YOU FEEL DO NOT HAVE ELECTRICAL WIRING EXPERIENCE, REFER TO A DO IT YOURSELF WIRING HANDBOOK OR HAVE YOUR FIXTURE INSTALLED BY A QUALIFIED LICENSED ELECTRICIAN.

**(2) GENERAL**

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning
2. All electrical connections must be in accordance with local codes, Ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. Those fixtures are intended to be mounted to a 4"x2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure.
4. Before starting the installation, disconnect the power by turning off the circuit or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

**Note:**

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution, and care are factors which cannot be built into any product. These factors must be supplied by the person(s).

**(3) UNPACK THE FIXTURE**

CHECK THE CONTENTS OF THE BOX YOU SHOULD RECEIVE:

- MOUNTING HARDWARE PACKAGE
- GLASS DIFFUSERS (NOT SUPPLIED ON ALL MODELS)
- FIXTURE ASSEMBLY

**(4) PREPARE THE FIXTURE**

**NOTE: FIRST TURN OFF ELECTRICITY**

Refer to figure 1 for illustration of fixture parts assembly.

1. If you are replacing an existing fixture disconnect and remove the old fixture. Expose the supply wires from the outlet box.
2. Attach supplied threaded screws (a) to the cross bar. Fasten cross bar to outlet box using supplied screws.
3. **ELECTRICAL CONNECTION:** Fix the ground fixture wire to the outlet box ground terminal (or to the outlet box ground wire). Connect the fixture wires to the appropriate electrical supply wires from the outlet box using wire connectors. Secure wire connectors with U.L. Listed electrical tape. Tuck wire carefully into outlet box.
4. Slide fixture base over long threaded screws (b) with washers and secure with supplied nuts (c) & (d). Tighten firmly.
5. Insert halogen bulb between sockets. Do not Touch The Halogen Bulb with Bare Hands. Use A Soft Dry Cloth. Fit supplied halogen tempered glass cover.
6. Fit glass diffuser to fixture base by inserting glass into two (2) clips and then securing with spring loaded clip.
7. Restore electricity and check operation of your new lighting fixture.

**CAUTION:**

**DO NOT USE LAMPS EXCEEDING MAXIMUM WATTAGE.**  
**AS PER CAUTION LABEL.**

